MAR.105

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM 10, OREGON within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)

State Well No. 3/1W - 32

State Permit No.

(1) OWNER:
Name James Smith
Address 66 N E Baldwin
Portland, Oregon

(2) LOCATION OF WELL:
County ~~Clackamas~~ Marion Driller's well number
¼ ¼ Section 32 T. 3S R. 1W W.M.
Bearing and distance from section or subdivision corner

(3) TYPE OF WORK (check):
New well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(6) CASING INSTALLED:
Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 66 ft. Gage
4" Diam. from 1 ft. to 66 ft. Gage
" Diam. from ft. to ft. Gage

(7) PERFORATIONS:
Perforated? ☒ Yes ☐ No
Type of perforator used Millknife - Torch
Size of perforations ¼ in. by 2 in.
80 perforations from 46 ft. to 54 ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(8) SCREENS:
Well screen installed ☐ Yes ☒ No
Manufacturer's Name
Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(9) CONSTRUCTION:
Well seal—Material used in seal Bentonite Mud
Depth of seal 20 ft. Was a packer used? no
Diameter of well bore to bottom of seal 10 in.
Were any loose strata cemented off? ☐ Yes ☒ No Depth
Was a drive shoe used? ☐ Yes ☒ No
Was well gravel packed? ☒ Yes ☐ No Size of gravel: ¼"
Gravel placed from 1 ft. to 66 ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? Depth of strata
Method of sealing strata off

(10) WATER LEVELS:
Static level 34 ft. below land surface Date 7/5/62
Artesian pressure lbs. per square inch Date

(11) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? driller
Yield: 10 gal./min. with 30 ft. drawdown after 8 hrs.
" " " "
" " " "
Bailer test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m. Date
Temperature of water Was a chemical analysis made? ☐ Yes ☒ No

(12) WELL LOG:
Diameter of well below casing
Depth drilled 66 ft. Depth of completed well 66 ft.
Formation: *Describe by color, character, size of material and structure, and show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.*

MATERIAL	FROM	TO
Surface	0	2
Brown sand	2	21
Cement gravel	21	30
Brown sandy clay	30	46
Broken sand and gravel (clay streaks)	46	60
Red clay	60	66

Work started June 28 1962. Completed July 5 1962
Date well drilling machine moved off of well July 19 1962

(13) PUMP:
Manufacturer's Name Rapidayton
Type: Submersible H.P. ½

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME John Truman Miller
(Person, firm or corporation) (Type or print)
Address P O Box 42 Hubbard, Oregon

Drilling Machine Operator's License No.

[Signed] John T. Miller
(Water Well Contractor)

Contractor's License No. 277 Date July 27, 1962

(USE ADDITIONAL SHEETS IF NECESSARY)